

ImagePerfect[™] 2506MPA Pro White Matt Polymeric Vinyl (FR)

ImagePerfect[™] 2506MPA Pro is a white matt polymeric vinyl incorporating PerfectApply technology and a permanent, grey adhesive for indoor and outdoor applications. It has been specially created for digital printing on large-format inkjet printers and is suitable for printing with eco solvent and solvent inks as well as UV-cured and latex inks.

ImagePerfect[™] 2506MPA Pro White Matt Polymeric Vinyl is a state-of-the-art permanent product for indoor and outdoor applications such as markings, decorations and vehicle graphics. It incorporates PerfectApply technology to increase repositionability and to facilitate bubble-free application. It promotes high levels of print quality with remarkable text definition and a large colour gamut to ensure colourful images with vibrant area infills. It features specific polymeric, non-migrating plasticizers and UV stabilizers, which ensure long-term outdoor durability and it is equipped with a backing paper that offers excellent lay flat properties. Additional opacity is provided by the grey adhesive. It must not be wet applied - i.e. dry application only. Laminate: IP 2810-101, IP 2810-200, IP 2810-300, IP 2830-106, IP 2830-109, IP 2830-200, etc.

Attention: Please make sure the printed IP 2506MPA Pro is completely dry before laminating. Before the IP 2506MPA Pro is applied, the surface should be completely cleaned. The use of IP Surface Cleaner (MIP1000) and the lint-free, IP Surface Cleaning Cloths (MMS8373) is a good match component cleaning solution to ensure that the surface is dry and free of dust and grease.

Specifications	
Description	Polymeric vinyl
Colour	White matt
Thickness	70mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent, grey
Adhesive Strength	18N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone paper, 140g/m ²
Temperature Range	-30°C to +90°C
Durability (unprinted)	8 years
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

Image: May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom

Information on physical and chemical characteristics and values in this document are based upon tests we believe to be reliable and do not constitute a warranty. They are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of stuch products for their specific use, including, but not limiting, but not limiting and are subject to change without prior notice. In case of any ambiguities or differences between the English and foreign versions of this document, the English version shall be prevailing and leading.

Elkon gives no express or implied guarantees or warranties with respect to the Products, including, but not limited to, any implied warranties of fitness for any particular use and/or non-infringement. All products are sold subject to Elkon's general terms and conditions of sale. Elkon's aggregate liability, whether for negligence, breach of contract, misrepresentation or otherwise, shall in no circumstances exceed the price of the defective, non-conforming, damaged or undelivered Products which give rise to such liability as determined by net price invoiced to Purchaser In respect of any coursence or series of occurrences. In the event of Improper use and/or incorrect processing that does not comply with our instructions, any and all liability is excluded. In no circumstances shall Elkon be liable for any indirect, incidental or consequential loss, damage or injury, including without limitation, loss of anticipated profits, goodwill, reputation, or losses or expenses resulting from third party claims.