CROWN OPTO S3



In front of you – technical information of our newest addition to Crown OPTO S family – Crown OPTO S3. Observing your fascinating interest with S family we have decided to extend the product line and provide you with modules for bigger depths as well. This is how S3 has emerged. With efficiency up to 103 lm/W, impressive distance between the modules, S3 should be considered when you want to illuminate boxes or letters of bigger depths.

APPLICATION

- Channel letters signs and light boxes
- Recommended depth 120 200 mm

FEATURES & BENEFITS

- Compact design
- Efficiency up to 103 lm/W
- IP67 protection class
- White, red, green and blue colours are available
- 5 year warranty


















GENERAL SPECIFICATIONS


SUPPLY VOLTAGE	12 VDC		
POWER	1.2 W, 1.5 W		
RECOMMENDED DEPTH	From 120 to 200 mm		
CC DISTANCE	340 mm		
BINNING	3 SDCM		
OPERATING TEMPERATURE	-30 °C ~ +50 °C		
STORAGE TEMPERATURE	-40 °C ~ +70 °C		
STORAGE CONDITIONS	Relative humidity <60%		
CERTIFICATION	CE and RoHS compliant		
IP CLASS	IP 67		
LIFETIME	L70 50,000 h		
WARRANTY	5 years (24/7)*		





* Dimensions are in mm

LIGHT DISTRIBUTION GRAPH



Beam angle: 160°

ORDERING INFORMATION

SKU	POWER, W	LUMEN OUTPUT, LM	COLOUR	STATUS
BMP-S3-03UH160CW651	1.5	155	6600 K	IN STOCK
BMP-S3-03UH160PW652	1.5	155	6500 K	IN STOCK
BMP-S3-03UH160NW401	1.5	152	4000 K	PRE-ORDER**
BMP-S3-03UH160WW301	1.5	152	3000 K	IN STOCK
BMP-S3-03UH160RC	1.2	52	red	PRE-ORDER**
BMP-S3-03UH160GC	1.5	100	green	PRE-ORDER**
BMP-S3-03UH160BC	1.5	27	blue	PRE-ORDER**

^{*} Pre-order products will be available only with M0Q from 3000 EUR, lead time 3 - 8 weeks. For precise lead time, contact your Customer Service manager.

	CHAIN		BAG	BOX
25 pcs	(net weight: 0.385 kg)	75 pcs	(net weight: 1.170 kg)	675 pcs (net weight: 11.000 kg)

© 2018, All rights reserved BaltLED, UAB. Specifications are subject to change without notice.