

ImagePerfect[™] 5700PA High Performance Film (FR)

ImagePerfect[™] 5700PA High Performance Film is a superior quality vinyl range incorporating PerfectApply technology and a permanent, solvent-based adhesive. This range is available in 25 colours, including black and white which are available in both a gloss finish and also a matt finish.

ImagePerfect™ 5700PA High Performance Film is suitable for a wide variety of indoor and long-term outdoor applications on flat and slightly curved surfaces, such as general purpose signage, window graphics, durable outdoor advertising, vehicle graphics, public transport advertising, sign systems, etc. It incorporates PerfectApply technology to increase repositionability and to facilitate bubble-free application, especially in the case of large, flat-panel installations. The specially-formulated, flexible, high performance films can be cut easily and weeded quickly. A permanent, solvent-based adhesive creates a strong final bond to ensure a secure and durable finish. The high-quality, PE-coated, silicone liner promotes excellent layflat, cutting and weeding characteristics. ImagePerfect™ 5700 High Performance Film with a gloss finish is also suitable for thermal transfer printing (with resin ribbons). In order to ensure the best results, this product must be dry applied. Please note that IP 5701 White Gloss and IP 5708 Black Gloss (i.e. the non-PA versions) are both certified to BS 5609 (Section Two) and they can, therefore, be considered for "marine use". Whilst none of the colours within the IP 5700PA range are certified, they would meet the requirements of BS 5609 (Section Two).

Specifications	
Description	High performance film
Colour	Black and white (gloss and matt) and 21 colours (gloss)
Thickness	70mym
Weight	N/A
Adhesive	Solvent based acrylic, permanent
Adhesive Strength	20N/25mm (Finat TM 1/24h)
Release Paper	PE-coated silicone liner, 140g/m²
Temperature Range	-30°C to +90°C
Durability (unprinted)	8 years (black and white) 7 years (clear and colours) 5 years (metallics)
Flame Retardancy	B-s1, d0
Shelf Life	2 years, 20°C / 50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF)

© May 2022 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners

For more information about ImagePerfect please visit www.imageperfect.com

Eikon Ltd, 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom