

## Imageperfect iD9 Gloss Laminate

## High-performance printable laminate with market-leading 9-year durability.

Engineered to protect and enhance your graphics, this laminate can be used with all iD9 Series polymeric films to preserve the vibrancy of prints. It comes with UV stabilisers, ensuring graphics maintain their colours and resist fading over the long term. Alternatively, you can also use this laminate as a printable clear film for window graphics and other glass applications. Imageperfect iD9 Gloss Laminate is manufactured with 28% less PVC than comparable films, incorporates a toluene-free adhesive, and is supplied in environmentally-responsible packaging.

Specifications	
Description	Long-term supersoft printable laminate
Colour	Clear
Finish	Gloss
Thickness	50μm
Weight	N/A
Adhesive Type	Solvent based acrylic, permanent
Adhesive Strength	16N/25mm (Finat TM 1/24h)
Release Paper	Double sided PE-coated silicone paper, 140gsm
Ink Compatibility	Eco-Solvent, Solvent, UV and Latex
Recommended Laminate	iD9 Gloss Laminate and iD9 Matt Laminate
Application method	Dry and wet application (wet application, only if used as a print film)
<b>Application Temperature</b>	Minimum +10°C
Temperature Range	-30°C to +90°C
Durability (unprinted)	9 years
Regulation	REACH Compliant
Flame Retardancy	B-s1, d0 (EN 13501-1)
Other Certifications	N/A
Shelf Life	2 years, 20°C/50% humidity
End of Life / Disposal	Not currently recyclable. Can be used for refuse derived fuel (RDF). Packaging can be recycled.

©September 2025 Eikon Ltd. Technical specifications are subject to change without prior notice. All trademarks mentioned are the property of their respective owners.

Attention: Please note that all print media should be acclimatised for a minimum of 24 hours to the same temperature and humidity as the printer room. Always perform a test print first. Please make sure the printed product is completely dry before further processing as laminating or application. Any residuals could affect the product performance. Before the product is applied, the surface should be completely cleaned and free of dust and grease and everything else that can have an influenceon on bond. Please do a test on the substrate before carrying out the application. The application information published by Imageperfect must be considered. The durability is based on middle European exposure conditions zone 1, vertikal. For more information about other, international areas please refere to the Imageperfect warranty sheet.

For more information about Imageperfect please visit **www.imageperfect.com** 38 Port Royal Avenue, Lune Industrial Estate, Lancaster. United Kingdom



