

# AUTO Drift

## AUTO Drift Laminate HD



The AUTO brand, exclusively from Spandex, is designed to cater for the ever-changing needs of professional wrappers, detailers and fleet applicators. The products are co-branded and have been developed in conjunction with leading manufacturers. The Auto Drift range has been manufactured by Orafol exclusively for Spandex.

### PRODUCT DESCRIPTION

Ultra-flexible transparent Premium Cast PVC film with the highest level of UV protection. Glossy or matt surface.

### RELEASE PAPER

Silicone coated paper, white, 90 g/m<sup>2</sup>.

### ADHESIVE

Solvent polyacrylate, permanent.

### AREA OF USE

For the indoor and outdoor protection of large format digital prints. The material is recommended for car wrapping, especially to rivets and corrugations because of its very good conformability, in combination with AUTO Drift.

Technical Data	
Thickness <sup>(1)</sup> (without paper and adhesive)	30 micron
Dimensional stability (FINAT TM 14)	Adhered to steel, shrinkage 0,1 mm max
Temperature resistance <sup>(3)</sup>	Adhered to aluminium, -50° C to +110° C, no variation
Resistance to solvents and chemicals	At room temperature, 72h after adhesion to aluminium, short-term resistance to most oils and greases, fuels, aliphatic solvents, weak acids, salts and alkalis
Adhesive power <sup>(1)</sup> (FINAT TM 1, after 24h stainless steel)	12 N/25 mm
Tensile strength (DIN EN ISO 527)	Along: min. 19 MPa Across: min. 19 MPa
Elongation at break (DIN EN ISO 527)	Along: min. 120% Across: min. 120%
Shelf life <sup>(2)</sup>	2 years
Application temperature	> +8° C
Service life by specialist application under vertical outdoor exposure (normal climate of central Europe)	8 years

(1) average (2) in original packaging, at 20°C and 50% relative humidity (3) normal climate of Central Europe

**Note:** Due to the diversity of prints and printing techniques, the user should test the suitability of ORAGUARD® laminating films for the specific print purpose, prior to use. Furthermore the application information published by ORAFOL must be followed.

**IMPORTANT NOTICE:** All ORAGUARD® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORAGUARD® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORAGUARD® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice. ORAGUARD® is a registered trademark of ORAFOL Europe GmbH.