

ORATAPE® MT95

Application Tape

Short description

Transparent mounting film on polyethylene basis with a finely grained surface for transferring punched or computer-cut lettering and symbols.

Front material

HDPE film, 0.095 mm

Adhesive

Polyacrylate, removable, Transparent, 0.025 mm

Technical properties

RESISTANCE

Shelf Life	2 Year(s)	in original packaging, at 20 °C and 50% relative humidity
Elongation at break	Minimum elongation at break along 450 % Minimum elongation at break across 450 %	DIN EN ISO 527
Tensile strength	Minimum tensile strength along 20 N/mm ² Minimum tensile strength across 20 N/mm ²	DIN EN ISO 527
Temperature resistance	Minimum temperature -40 °C Maximum temperature 80 °C	Short-term exposure up to 100 °C

ADHESIVE PROPERTIES

Adhesive power	2 N/25 mm	after 20 min, stainless steel FINAT TM 1, average value
----------------	-----------	---

PROCESSING

Application temperature	Minimum temperature 10 °C
-------------------------	---------------------------

ORATAPE® MT95

Application Tape

IMPORTANT NOTES

All ORATAPE® products are subject to careful quality control throughout the manufacturing process. It is guaranteed that the products are delivered in merchantable quality and free of manufacturing defects. The traceability of our goods in accordance with ISO 9001 is ensured by means of the roll number. The information published on ORATAPE® products is based on research results which the company believes to be reliable but does not constitute a guarantee. Because of the wide variety of uses of ORATAPE® products and the continuing development of new applications, it is the responsibility of the purchaser to carefully evaluate the suitability and performance of the product for its intended use. Furthermore, the processing instructions issued by ORAFOL must be observed. The purchaser bears all risks arising from the use of these products. All information is subject to change without notice. ORATAPE® is a registered trademark of ORAFOL Europe GmbH.