

Description

This transfer tape consists of a highly transparent pure acrylate adhesive with an excellent resistance to ultraviolet radiation, extreme temperatures, chemicals, solvents and humidity. Its high shear transfer adhesive is extremely durable on metal, varnish and high energy surfaces.

Carrier

without

Liner

Double lined with brown paper, coated with silicone and polyethylene

Adhesive

Pure acrylate

Area of use

Ideal as an adhesive medium for signs, decorations, front plates and displays that require an extremely high shear strength, adhesion strength and temperature resistance. For adhesion to rough, structured and stamped surfaces. The Transfer Tape is certified according to UL 969.

Technical Data

Thickness* (adhesive without liner)	120 micron
Temperature resistance***	-40° C to +170° C, for short periods up to +200° C
Adhesive power* (FINAT TM 1, on stainless steel, one side covered with 50 micron polyester film)	17 N/25 mm after 1 min 22 N/25 mm after 20 min 24 N/25 mm after 24 h
Shear strength* (FINAT TM 8, on stainless steel, one side covered with 50 micron polyester film)	> 1000 h at 23° C > 72 h at 70° C
Shelf life**	2 years
Application temperature	> +18° C

* average ** in original packaging, at 20° C and 50% relative humidity *** normal climate of Central Europe

IMPORTANT NOTICE

All ORABOND® products are subject to careful quality control throughout the manufacturing process and are warranted to be of merchantable quality and free from manufacturing defects. Published information concerning ORABOND® products is based upon research which the Company believes to be reliable although such information does not constitute a warranty. Because of the variety of uses of ORABOND® products and the continuing development of new applications, the purchaser should carefully consider the suitability and performance of the product for each intended use, and the purchaser shall assume all risks regarding such use. All specifications are subject to change without prior notice.

ORABOND® is a registered trademark of ORAFOL Europe GmbH.